



NEENAH COLDENHOVE

Jetcol® TA ■ SUBLIMATION TRANSFER PAPER ■

Jetcol® Thermal Adhesive (TA) is a great example of our dedication to the dye sublimation industry. We developed this product in close cooperation with our customers, to help solve one of the biggest issues in their daily operation: ghosting. Jetcol® Thermal Adhesive (TA) is a specially coated paper grade which makes the paper stick firmly to the textile during the sublimation process – without leaving a sticky residue on the textile.



Worldwide
availability



Premium
quality



Cost efficient
solution



Your sustainable
partner

Jetcol® TA ■ SPECIFICATION



SUSTAINABILITY



Thanks to our in-house water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Currently all energy required by the factory comes out of energy released during the production of paper. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

CERTIFICATIONS



The mark of responsible forestry



ISO 9001
ISO 14001
ISO 45001
BUREAU VERITAS
Certification

JETCOL® TA

- Adhesive paper
- Suitable for various of elastic fabrics
- Avoids ghosting and shadow lines

GSM 85 / 105

Ink coverage

Transfer yield

Dry speed

GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for plotter printers using water based sublimation inks.

RECOMMENDED PRINT ROOM SETTINGS

- Ideal printing room temperature is 23°C and 50% relative humidity.
- Maintaining ideal printing room climatic conditions for good dimensional stability, flatness of paper and faster ink drying.

RECOMMENDED TRANSFER SETTINGS



Temperature: 195-205°C
Time: 25-40 seconds

Ideal settings might vary depending on the process, print environment and textiles.

AVAILABILITY

PRODUCT	TYPE	WIDTH		LENGTH		DIAMETER	
		MM	INCH	M	FT	MM	INCH
TA 85 g/m ²	plotter	1320	52	140	459	165	6,5
TA 85 g/m ²	plotter	1620	64	140	459	165	6,5
TA 105 g/m ²	plotter	1118	44	100	328	145	5,5
TA 105 g/m ²	plotter	1620	64	110	361	165	6,5
TA 105 g/m ²	plotter	1620	64	150	492	190	7,5

Standard Core is 76 mm / 3 inch.

For TA 105 g/m², plotter rolls 1118 mm / 44 inch have Core 50 mm / 2 inch.

Other sizes or special dimensions are available on request. Anyone interested can contact the licensed agent or Neenah Coldenhove sales representative.

SHELF LIFE	This product is covered with a guarantee of 1 year after receiving the product under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.
STORAGE AND HANDLING	<ul style="list-style-type: none"> Store material in original packaging only. Avoid exposure to direct sunlight and extreme weather conditions. Place the roll to be printed in printing room at least 24 hours prior to printing. Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable. For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, this may in some cases bend the core bar.



Scan the QR code for instructional video or go to the link www.neenahcoldenhove.com

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and pressed with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Neenah Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.