



# Xtreme® Light ■ SUBLIMATION TRANSFER PAPER ■

Xtreme® LIGHT is a low weight paper designed for the fast industrial printers producing fashion with lower ink coverages. Due to the lower weight this paper is especially suitable for printing companies who deliver their printed paper all over the world by air transportation.



Worldwide availability



Premium quality



Cost efficient solution




Your sustainable partner

## Xtreme® Light ■ SPECIFICATION



- More meters/yards on a roll
- High transfer yield
- Low transportation costs of printed paper\*



<sup>\*</sup>Only available under specific terms & conditions.

#### **GENERAL**

- The outside of the roll is the coated side / printing side.
- Suitable for industrial and plotter printers using water-based sublimation inks.

#### RECOMMENDED TRANSFER SETTINGS



Temperature: 195-205°C Time: 25-40 seconds

Ideal settings might vary depending on the process, print environment and textiles.

#### **RECOMMENDED PRINT ROOM SETTINGS**

- Ideal printing room temperature is 23°C and 50% relative humidity.
- Maintaining ideal printing room climatic conditions for good dimensional stability, flatness of paper and faster ink drying.

	print driving in the textilied			
		ľ		
AVAII ARII ITY				

AVAILABILITY								
TYPE	PE WIDTI		LEN	GTH	DIAMETER			
	MM	INCH	M	FT	MM	INCH		
mini jumbo	1620	64	2000	6562	380	15		
mini jumbo	1620	64	2500	8202	450	18		
jumbo	1620	64	10700	35105	900	35,5		

Standard Core is 76 mm / 3 inches.

Other sizes or special dimensions are available on request. Anyone interested can contact the licensed agent or Neenah Coldenhove sales representative.

SHELF LIFE	This product is covered with a guarantee of 1 year after receiving the product under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.
STORAGE AND HANDLING	Store material in original packaging only. Avoid exposure to direct sunlight and extreme weather conditions. Place the roll to be printed in printing room at least 24 hours prior to printing. Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable. For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, this may in some cases bend the core bar.

### **Xtreme**®

#### **SUSTAINABILITY**



Thanks to our inhouse water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Currently all energy required by the factory comes out of energy released during the production of paper. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

#### **CERTIFICATIONS**







Scan the QR code for instructional video or go to the link www.neenahcoldenhove.com

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and pressed with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Neenah Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.